



Hummel Croton Inc.
10 Harmich Rd.
South Plainfield, NJ 07080
www.HummelCroton.com
Phone: 908-754-1800
Fax: 908-754-1815

In Case Of Emergency Call
(U.S.) 800-424-9300
(International) +1-813-248-3924

Sulfur Safety Data Sheet

1. Product and Company

Product name: Sulfur
Synonym: Sulphur, Brimstone
CAS-No.: 7704-34-9
Company: Hummel Croton Inc.
10 Harmich Rd.
South Plainfield, NJ 07080
Telephone: 908-754-1800
Fax: 908-754-1815

HMIS Rating	
Health	1
Flammability	1
Reactivity	0
Personal Protection	E

Emergency telephone number

Emergency Phone #: Chemtrec US: 800-424-9300
ChemTel International: +1-813-248-0585

2. Hazards

GHS Label Elements

GHS Classification: Skin Irritation (Category 2), H315

Pictogram(s)



Signal word **WARNING**

Hazard statement(s)

H315 Causes skin irritation

Precautionary statement(s)

- P264 Wash skin thoroughly after handling.
P280 Wear protective gloves.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P321 Specific treatment (see supplemental first aid instructions on this label).
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Hazards not otherwise classified (HNOC) or not covered by GHS

Combustible dust.

3. Composition/Ingredients

Substance
Formula: S
Molecular weight: 32.06 g/mol
CAS-No.: 7704-34-9

Material	CAS	%	OSHA	ACGIH
Sulfur	7704-34-9	100%	15 mg/m ³ as Nuisance Dust	15 mg/m ³ as Nuisance Dust

4. First Aid

First Aid For Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

First Aid For Skin: In case of contact, flush skin with water. Wash clothing before reuse. Call a physician if irritation occurs.

First Aid For Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

First Aid For Ingestion: If swallowed, call a physician immediately.

5. Fire Data

Flammability: Non-Flammable

Flash Point: Not Applicable

Auto Ignition: 458-511°F

Flammable Limits: Not Applicable

Extinguishing Media: Water, foam or sand.

Fire Fighting Procedure: Sulfur melts and flows when burning and evolves large quantities of highly toxic, irritating and suffocating sulfur dioxide. Do not enter any enclosed or confined fire space without proper protective equipment including self-contained breathing apparatus. In case of fire, firemen must use a full face, self-contained breathing apparatus (Scott Air Pak or equivalent) and suitable protective equipment. Cool area on fire with fog nozzle spray as fire may rekindle if burning mass is not cooled below 300°F (140°C).

Fire/Explosion Hazards: The primary hazard in handling powdered sulfur is that sulfur dust is suspended in air ignites easily and produces explosive forces in confined areas. Ignition sources can be heat, friction, pyrophoric sulfur and internally generated static electricity. An initial small explosion can create subsequent larger explosions if the building area contains dusty powder residue on overhead surfaces such as rafters or trusses. A sulfur dust explosion will produce Sulfur Dioxide, a toxic gas. MINIMUM EXPLOSIVE CONCENTRATION: 0.350 gms/m³ MINIMUM SPARK ENERGY FOR IGNITION: 15 millijoules

6. Accidental Release

Spill Or Leak Procedures: Utilize recommended protective clothing and equipment. Clean spills in a manner that does not disperse dust into the air. Spill area can be washed with water. Collect wash water for approved disposal. Keep from entering water or ground water.

7. Handling And Storage

Storage Temperatures: Store at ambient temperature

Shelf Life: Unlimited in tightly sealed container

Special Sensitivity: None.

Handling/Storage Precautions: Avoid breathing dust. Avoid getting in eyes or on skin. Wash thoroughly after handling. Store in a dry place away from direct sunlight, heat and incompatible materials. Reseal containers immediately after use. Store away from food and beverages.

8. Exposure Controls/Personal Protection

Eye Protection: Safety glasses or goggles.

Skin Protection: PVC gloves with impervious boots, apron or coveralls. Wash hands and face before eating, drinking or using tobacco.

Respirator: Work ambient concentrations should be monitored and if the recommended exposure limit is exceeded, a NIOSH/MSHA approved dust respirator must be worn.

Ventilation: Use local ventilation if dusting is a problem, to maintain air levels below the recommended exposure limit.

Additional Measures: Emergency showers and eye wash stations should be available. Educate and train employees in the safe handling of hazardous chemicals.

9. Physical And Chemical Properties

Physical Form: Powder

Color: Yellow

Odor: Slight odor

Molecular Weight: 32.06 g/mol

Boiling Point: 444°C

Melting/Freezing Point: 242-251°F

Solubility In Water: Insoluble

Specific Gravity: 2.04-2.07

10. Stability And Reactivity

Stability: Stable.

Hazardous Polymerization: Will not occur.
Incompatibilities: No specific incompatibilities known.
Instable Conditions: Excessive temperatures (see incompatibilities).
Decomposition Temperature: Begins to decompose 300°C
Decomposition Products: Thermal decomposition may produce carbon monoxide, ammonia, oxides of nitrogen, oxides of phosphorous and/or hydrogen cyanide.

11. Toxicological Information

RTECS Number: WS4250000
Routes of Exposure: Eye contact. Ingestion. Inhalation. Skin contact.
Toxicity Data: Ihl-Mam LC50: 1660 mg/m³
Chronic Toxic Effects: This product has no known chronic effects. Repeated or prolonged exposure to this compound is not known to aggravate medical conditions.
Acute Toxic Effects: Irritating to the skin and eyes on contact. Inhalation will cause irritation to the lungs and mucus membrane. Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are characteristics of skin inflammation. Follow safe industrial hygiene practices and always wear protective equipment when handling this compound.

12. Ecological Information

Ecotoxicity: Not available at this time.

13. Disposal Considerations

Waste Disposal Method: Waste disposal should be in accordance with existing federal, state and local environmental regulations.

14. Transportation Information

Domestic
Proper Shipping Name: Sulfur
UN Number: NA1350
Class: 9
P.G.: III
Label Code: 9

International
Proper Shipping Name: Sulfur
UN Number: UN1350
Class: 4.1
P.G.: III
Label Code: 4.1

15. Regulatory Information

OSHA Status: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Chemical Inventory: This compound is on the EPA Toxic Substance Control Act (TSCA) Inventory List

California Proposition 65: To the best of our knowledge, this product contains no levels of listed substances, which the State of California has found to cause cancer, birth defects or other reproductive effects.

SARA 313 Title III:

Section 320 Extremely Hazardous Substances: None

Section 311/312 Hazardous Categories: None

Section 313 Toxic Chemicals: None

16. Other Information

Prepared By: Michael Richard

Date: March 21, 2018

Reason For Issue: Emergency Contact Update

No warranty, expressed or implied, or merchantability, fitness for a particular purpose or otherwise is made, except that the products herein discussed comply with the chemical description on the labels. Buyer assumes risks of the use, storage and handling. Hummel Croton shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge, true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions. This information is not to be taken as a license to operate under, or a recommendation to infringe any patent(s). The observance of all regulations and patents is the responsibility of the user. No agent, representative or employee of this company is authorized to vary any items of this notice.