



Hummel Croton Inc.
10 Harmich Road
South Plainfield, NJ 07080

Tel:908-754-1800 / Fax 908-754-1815

MSDS



Aluminum Powder Flitters

In case of Emergency Call Chemtrec®
(U.S.) (800)-424-9300
(International) (703)-527-3887

Section I. Chemical Product and Company Identification

Supplier:

Hummel Croton Inc.
10 Harmich Road
South Plainfield, NJ 07080
(908)-754-1800

Chemical Name: Aluminum

Synonym: Aluminum Powder Flitters

CAS Number: 7429-90-5

Chemical Formula: Al

HMIS Rating

Health	0
Flammability	4
Reactivity	1
Personal Protection	E

Section II. Composition and Information on Ingredients

Material	CAS#	%	OSHA	ACGIH
Aluminum	7429-90-5	85-99%	15 mg(Al)/m ³	15 mg(Al)/m ³
Aluminum Oxide	1344-28-1	0.5-10%	10 mg/m ³	10 mg/m ³
Carbon	1333-86-4	85-99%	3.5 mg/m ³	3.5 mg/m ³
Stearic Acid	57-11-4	85-99%	Not Established	Not Established

Section III Hazards Identification:

Acute Health Effects: Irritating to the skin and eyes on contact. Inhalation will cause irritation to the lungs and mucus membrane. Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are characteristics of skin inflammation. Follow safe industrial hygiene practices and always wear protective equipment when handling this compound.

Chronic Health Effects: This product has no known chronic effects. Repeated or prolonged exposure to this compound is not known to aggravate medical conditions.

Acute Health Effects: This product is not listed by NTP, IARC or regulated as a Carcinogen by OSHA.

Section IV. First Aid Measures

First Aid For Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

First Aid For Skin: In case of contact, flush skin with water. Wash clothing before reuse. Call a physician if irritation occurs.

First Aid For Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

First Aid For Ingestion: If swallowed, call a physician immediately.

Section V. Fire and Explosion Data

Flammability: Non-Flamable

Flash Points: Not Applicable

Auto-Ignition: 1400°F (759°C)

Flammable Limits: LEL%: 0.04 oz/ft³ UEL%: N/A

Extinguishing Media: Dry Chemical Powder. Dry Sand. DO NOT USE WATER.

Fire Fighting Procedure: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes

Fire/Explosion Hazards: Emits toxic fumes under fire conditions. Do not expose to air and fire. This material, like most materials in powder form, is capable of creating a dust explosion. DO NOT DISTURB METAL WHILE EXTINGUISHING THE FIRE.

Section VI. Accidental Release Measures

Spill Or Leak Procedures: Utilize recommended protective clothing and equipment. Clean spills in a manner that does not disperse dust into the air. Spill area can be washed with water. Collect wash water for approved disposal. Keep from entering water or ground water

Section VII. Handling and Storage

Storage Temperatures: Store at ambient temperature

Shelf Life: Unlimited in tightly closed container.

Special Sensitivity: None

Handling/Storage Precautions: Avoid breathing dust. Avoid getting in eyes or on skin. Wash thoroughly after handling. Store in a dry place away from direct sunlight, heat and incompatible materials (see Section X). Reseal containers immediately after use. Store away from food and beverages.

Section VIII. Exposure Controls/Personal Protection

Eye Protection: Safety glasses or goggles.

Skin Protection: PVC gloves with impervious boots, apron or coveralls. Employees should wash their hands and face before eating, drinking or using tobacco products.

Respirator: Work ambient concentrations should be monitored and if the recommended exposure limit is exceeded, a NIOSH/MSHA approved dust respirator must be worn.

Ventilation: Use local ventilation if dusting is a problem, to maintain air levels below the recommended exposure limit.

Additional Protective Measures: Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous chemicals.

Section IX. Physical and Chemical Properties

Physical Form: Powder or Flitter

Color: Silver

Odor: Odorless

Molecular Weight: 26.98

Boiling Point: 2630°C (4766°F)

Melting/Freezing Point: 660°C (1220°F)

Solubility In Water: Insoluble

Specific Gravity: 2.6

Section X. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will Not occur

Incompatibilities: Acids, acid chlorides, alkalis, oxidizing agents, halogens, air sensitive, moisture sensitive

Instable Conditions: Excessive temperatures (see Incompatibilities).

Decomposition Temperature: Not Established

Decomposition products: Toxic fumes of aluminum oxide Could react with water, acids, and alkalis to form combustible hydrogen gas.

Section XI. Toxicological Information

RTECS Number: BD0330000

Routes of Exposure: Eye contact. Ingestion. Inhalation. Skin contact.

Toxicity Data: LD50: Not Determined

Chronic Toxic Effects: Not known to cause any long term harmful health effects

Acute Toxic Effects: Mild irritant to skin, eyes and respiratory system

Section XII. Ecological Information

Ecotoxicity: This product may cause adverse environmental effects. Employ management practices which prevent material from contacting stormwater, entering waterway, or otherwise impacting plant and animal species.

Section XIII. Disposal Considerations

Waste Disposal Method: Waste disposal should be in accordance with existing federal, state and local environmental regulations.

Section XIV. Transportation Information

Proper Shipping Name: Aluminum

UN Number: 1309

Class: 4.1

P.G.: II

Label Code: 4.1

Section XV. Regulatory Information

OSHA Status: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Chemical Inventory: This compound is on the EPA Toxic Substance Control Act (TSCA) inventory List

California Proposition 65: To the best of our knowledge, this product contains no levels of listed substances, which the state of California has found to cause cancer, birth defects or other reproductive effects.

SARA 313 Title III:

Section 302 Extremely Hazardous Substances: None

Section 311/312 Hazardous Categories: None

Section 313 Toxic Chemicals: This product may be subject to reporting requirement. (Contains 100% AI)

Section XVI. Other Information

Prepared By: Mark Dugan

Date: January 05, 2009

Reason For Issue: Updated Format

No warranty, expressed or implied, or merchantability, fitness for a particular purpose or otherwise is made, except that the products herein discussed comply with the chemical description on the labels. Buyer assumes risks of the use, storage and handling. Hummel shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge, true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions. This information is not to be taken as a license to operate under, or a recommendation to infringe any patent(s). The observance of all regulations and patents is the responsibility of the user. No agent, representative or employee of this company is authorized to vary any terms of this notice.