### **MSDS**



In case of Emergengy Call Chemtrec ® (U.S.) (800)-424-9300 (International) (703)-527-3887

### Silicon Powder

# Section I. Chemical Product and Company Identification

Supplier:

Hummel Croton Inc. 10 Harmich Road South Plainfield, NJ 07080 (908)-754-1800

Chemical Name: Silicon

Synonym: Silicon Metal Powder

CAS Number: 7440-21-3 Chemical Formula: Si

# HMIS Rating Health 1 Flammability 2 Reactivity 1 Personal Protection E

# **Section II. Composition and Information on Ingredients**

Material	CAS#	%	OSHA	ACGIH
Silicon	7440-21-3	97-99%	10mg/m³ Total Dust	10mg/m³
Aluminum	7429-90-5	<1%	15mg/m³ Total Dust	5mg/m³
Iron Oxide Fummed	7439-89-6	<1%	10mg/m³ Total	10mg/m³

### Section III Hazards Identification:

Accute Health Effects: Irritating to the skin and eyes on contact. Inhalation will cause irritation to the lungs and mucus membrane. Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are characteristics of skin inflammation. Follow safe industrial hygiene practices and always wear protective equipment when handling this compound.

Chronic Health Effects: This product has no known chronic effects. Repeated or prolong exposure to this compound is not known to aggravate medical conditions.

Accute Health Effects: This product is not listed by NTP, IARC or regulated as a Carcinogen by OSHA.

### Section IV. First Aid Measures

First Aid For Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

First Aid For Skin: In case of contact, flush skin with water. Wash clothing before reuse. Call a physician if irritation occurs.

First Aid For Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

First Aid For Ingestion: If swallowed, call a physician immediately.

### **Section V. Fire and Explosion Data**

Flammability: Non-Flamable Flash Points: Not Applicable

Auto-Ignition: Dust Layer Approx. 1650°F (900°C)

Flammable Limits: Not Applicable

Extinguishing Media: Class D Fire: Use dry powder, dry sand, or carbon dioxide to smother Fire.

Fire Fighting Procedure: Fire may also be isolated and allowed to burn itself out. Do not disturb burning metal while extinguishing the

fire.

Fire/Explosion Hazards: Lump material is not combustible. When suspended in air, dusts of silicon metal can be readily ignited, propagate flame, and generate some pressure or explode. The degree of combustibility in air is dependent upon particle size, oxide coating, and quality of dispersion. The hazard increases with particle fineness. Avoid generating sparks or ignition sources in areas of high airborne dust levels or in areas with accumulated dust. Thoroughly clean areas or equipment to be maintained prior to dust disturbing or ignition source generation activities.

### Section VI. Accidental Release Measures

Spill Or Leak Procedures: Utilize recommended protective clothing and equipment. Clean spills in a manner that does not disperse dust into the air. Spill area can be washed with water. Collect wash water for approved disposal. Keep from entering water or ground water

# Section VII. Handling and Storage

**Storage Temperatures:** Store at ambient temperature **Shelf Life:** Unlimited in tightly closed container.

Special Sensitivity: None

Handling/Storage Precautions: Avoid breathing dust. Avoid getting in eyes or on skin. Wash thoroughly after handling. Store in a dry place away from direct sunlight, heat and incompatible materials (see Section X). Reseal containers immediately after use. Store away from food and beverages.

# **Section VIII. Exposure Controls/Personal Protection**

Eye Protection: Safety glasses or goggles.

Skin Protection: PVC gloves with impervious boots, apron or coveralls. Employees should wash their hands and face before eating, drinking or using tobacco products.

**Respirator:** Work ambient concentrations should be monitored and if the recommended exposure limit is exceeded, a NIOSH/MSHA approved dust respirator must be worn.

Ventilation: Use local ventilation if dusting is a problem, to maintain air levels below the recommended exposure limit.

Additional Protective Measures: Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous chemicals.

# **Section IX. Physical and Chemical Properties**

Physical Form: Solid

Color: Silvery Metal Powder

Odor: Odorless

Molecular Weight: 28.08
Boiling Point: Not Applicable
Melting/Freezing Point: 1440°C
Solubility In Water: Insoluble
Specific Gravity: 2.3

### Section X. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will Not occur Incompatibilities: Acids and strong bases

Instable Conditions: Excessive temperatures (see Incompatibilities).

Decomposition Temperature: N/A
Decomposition products: N/A

## Section XI. Toxicological Infomation

RTECS Number: VW 0400000

Routes of Exposure: Eye contact. Ingestion. Inhalation. Skin contact.

Toxicity Data: Orl-Rat LD50: 3160 mg/kg

Chronic Toxic Effects: This product has no known chronic effects. Repeated or prolong exposure to this compound is not known to

aggravate medical conditions.

Acute Toxic Effects: Irritating to the skin and eyes on contact. Inhalation will cause irritation to the lungs and mucus membrane. Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are characteristics of skin inflammation.

Follow safe industrial hygiene practices and always wear protective equipment when handling this compound.

### Section XII. Ecological Information

Ecotoxicity: Not available at this time.

## Section XIII. Disposal Considerations

Waste Disposal Method: Waste disposal should be in accordance with existing federal, state and local environmental regulations.

# Section XIV. Transportation Information

Proper Shipping Name: Silicon Crystalline

UN Number: N/A Class: N/A P.G.: N/A Label Code: N/A

### Section XV. Regulatory Information

OSHA Status: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR

1910.1200.

TSCA Chemical Inventory: This compound is on the EPA Toxic Substance Control Act (TSCA) inventory List

California Proposition 65: To the best of our knowledge, this product contains no levels of listed substances, which the state of California has found to cause cancer, birth defects or other reproductive effects.

SARA 313 Title III:

Section 302 ExtremelyHazardous Substances: None Section 311/312 Hazardous Categories: None

Section 313 Toxic Chemicals: None

### Section XVI. Other Information

Prepared By: Mark Dugan Date: January 05, 2009

Reason For Issue: Updated Format

No warranty, expressed or implied, or merchantability, fitness for a particular purpose or otherwise is made, except that the products herein discussed comply with the chemical description on the labels. Buyer assumes risks of the use, storage and handling. Hummel shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge, true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions. This information is not to be taken as a license to operate under, or a recommendation to infringe any patent(s). The observance of all regulations and patents is the responsibility of the user. No agent, representative or employee of this company is authorized to vary any terms of this notice.